

## 9002N SLED9002N BRANCA FITA 19WM 5500K 80 - 1m



Luminária linear de embutir em forro de gesso ou Dry-wall com iluminação difusa. Corpo em alumínio extrudado com acabamento na cor branca. Difusor em acrílico extrudado leitoso. Indicado para residência, recepção, escritório etc.

Fluxo luminoso – 836 lm/m

Potência – 4,8 W/m

Intensidade pico – 330cd

CCT – 5724K



IRC – 84,7

Coordenada CIE 1931 – x- 0,328 y- 0,339

A x L - 31x29

Peso - 0,35kg/m


IP - 20 - Uso Interno

IK - 00 – Não aplicável

Alimentação - 12vdc

Data do ensaio

09/03/2022 16:06:12



Facho de abertura

**102,6°**


**Rf 82,5**



Fidelity index Rf

**Rg 92,0**


Gamut index Rg

Hue Bin	R <sub>f</sub>	Shifts (%)	
		Chroma	Hue
1	75	-12%	2%
2	85	-6%	6%
3	84	-4%	7%
4	88	-3%	2%
5	87	-6%	0%
6	93	-4%	-2%
7	86	-9%	0%
8	81	-9%	7%
9	79	-8%	17%
10	72	-2%	17%
11	77	5%	13%
12	92	5%	-1%
13	85	6%	-9%
14	83	0%	-10%
15	71	2%	-25%
16	85	-8%	-2%






TM-30: 82,5



CRI: 84,7 (R1-R8)



CRIRA R1-R8 / CRIre R1-R15

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
84,4	94,0	94,4	80,1	83,1	87,6	85,4	68,8	16,8	83,2	79,3	58,7	88,2	97,8	79,5

TM30 valores C. 16 valores extraídos dos 99.

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
75,1	84,5	83,9	87,6	86,9	92,5	85,8	80,6	79,2	71,9	77,2	91,5	85,1	82,9	70,6	84,7

## Parametros de cor

Temperatura de cor	Índice de reprodução de cor	Reprodução de cor vermelho R9	Color fidelity	Color gamut	Color quality scale	Coordenada de cor cie 1931	Coordenada de cor cie 1931	Coordenada de cor	Coordenada de cor	Color deviation from black body
CCT	IRC	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	$\Delta uv$
5724 K	84,7	16,8	82,5	92,0	80,8	0,328	0,339	0,204	0,317	0,0020







**Rf 82,5**

Fidelity index Rf

**Rg 92,0**

Gamut index Rg

Hue Bin	R <sub>i</sub>	Shifts (%)	
		Chroma	Hue
1	75	-12%	2%
2	85	-6%	6%
3	84	-4%	7%
4	88	-3%	2%
5	87	-6%	0%
6	93	-4%	-2%
7	86	-9%	0%
8	81	-9%	7%
9	79	-8%	17%
10	72	-2%	17%
11	77	5%	13%
12	92	5%	-1%
13	85	6%	-9%
14	83	0%	-10%
15	71	2%	-25%
16	85	-8%	-2%



Avaliação todas as amostras de cores

Glare Evaluation According to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X    Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	27,7	28,9	28,0	29,2	29,4	25,7	26,9	26,0	27,2	27,4
	3H	29,2	30,4	29,6	30,7	30,9	26,3	27,5	26,7	27,8	28,0
	4H	29,8	31,0	30,2	31,2	31,5	26,5	27,6	26,9	27,9	28,2
	6H	30,3	31,3	30,7	31,6	32,0	26,7	27,7	27,1	28,0	28,4
	8H	30,5	31,4	30,8	31,8	32,2	26,8	27,8	27,2	28,1	28,5
	12H	30,6	31,5	30,9	31,8	32,3	26,8	27,8	27,2	28,1	28,6
4H	2H	28,0	29,1	28,4	29,4	29,7	26,4	27,5	26,8	27,8	28,1
	3H	29,8	30,7	30,1	31,0	31,5	27,2	28,1	27,6	28,5	28,9
	4H	30,4	31,3	30,9	31,7	32,3	27,4	28,2	27,8	28,7	29,2
	6H	31,0	31,8	31,5	32,2	32,5	27,6	28,5	28,2	28,8	29,2
	8H	31,1	31,9	31,7	32,3	32,7	27,8	28,5	28,3	28,9	29,3
	12H	31,3	31,9	31,8	32,3	32,8	27,8	28,4	28,3	28,9	29,4
8H	4H	30,4	31,2	31,0	31,6	32,0	27,6	28,4	28,1	28,8	29,2
	6H	31,1	31,6	31,6	32,1	32,7	28,0	28,6	28,5	29,0	29,6
	8H	31,3	31,8	31,9	32,4	33,0	28,2	28,7	28,7	29,2	29,9
	12H	31,5	31,9	32,1	32,5	33,1	28,4	28,8	29,0	29,3	29,9
12H	4H	30,4	31,0	30,9	31,5	32,0	27,6	28,2	28,1	28,7	29,2
	6H	31,1	31,6	31,6	32,1	32,8	28,1	28,6	28,6	29,1	29,8
	8H	31,3	31,7	31,9	32,3	32,9	28,3	28,7	28,9	29,2	29,9
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,1 / -0,1					0,2 / -0,3				
S = 1.5H		0,2 / -0,3					0,4 / -0,7				
S = 2.0H		0,6 / -0,7					0,9 / -1,5				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 836 lm total luminous flux											


**Coeficiente de utilização**

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	101	101	101	99
1	109	105	101	97	106	102	99	96	98	95	92	94	91	89	90	88	86	84
2	100	92	86	80	97	90	84	79	86	82	77	83	79	75	80	77	73	71
3	91	81	74	68	89	80	73	67	77	71	66	74	69	64	71	67	63	61
4	84	73	64	58	82	71	63	57	69	62	56	66	60	55	64	59	55	52
5	77	65	56	50	75	64	56	50	62	55	49	60	53	48	58	52	48	46
6	72	59	50	44	70	58	50	44	56	49	43	54	48	43	52	47	42	40
7	67	53	45	39	65	53	45	39	51	44	38	49	43	38	48	42	38	36
8	62	49	41	35	60	48	40	35	47	40	34	45	39	34	44	38	34	32
9	58	45	37	31	57	44	37	31	43	36	31	42	36	31	41	35	31	29
10	54	41	34	29	53	41	34	29	40	33	28	39	33	28	38	32	28	26

**Quantidade de luminárias**

**Luminaire budgetary diagram**





### Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
330lx	82lx	37lx	21lx	13lx	9lx	7lx	5lx	4lx	3lx	3lx	2lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx
30,6fcd	7,7fcd	3,4fcd	1,9fcd	1,2fcd	0,9fcd	0,6fcd	0,5fcd	0,4fcd	0,3fcd	0,3fcd	0,2fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd

### Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
330	328	324	316	306	294	278	261	241	220	198	173	147	120	92	64	39	17	3	2
100%	99%	98%	96%	93%	89%	84%	79%	73%	67%	60%	52%	45%	36%	28%	20%	12%	5%	1%	1%

### Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
330	329	325	316	299	280	256	231	204	175	146	117	88	60	36	23	17	8	1	1
100%	100%	98%	96%	91%	85%	78%	70%	62%	53%	44%	35%	27%	18%	11%	7%	5%	2%	0%	0%

### Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
330	328	324	316	306	294	278	261	241	220	198	173	147	120	92	64	39	17	3	2
100%	99%	98%	96%	93%	89%	84%	79%	73%	67%	60%	52%	45%	36%	28%	20%	12%	5%	1%	1%

### Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
330	329	325	316	299	280	256	231	204	175	146	117	88	60	36	23	17	8	1	1
100%	100%	98%	96%	91%	85%	78%	70%	62%	53%	44%	35%	27%	18%	11%	7%	5%	2%	0%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
102,6°	150°	171,1°	82,3%	58,1%

**iso-candela diagram**




10%	33 cd
20%	66 cd
30%	99 cd
40%	132 cd
50%	165 cd
60%	198 cd
70%	231 cd
80%	264 cd
90%	297 cd

Conditions:

Number of c-planes: 16

Candela at center: 330 cd

**iso-lux diagram**



3%	98,9m lx
5%	0,165 lx
10%	0,330 lx
30%	0,989 lx
50%	1,65 lx

Conditions:

Number of c-planes: 16

Lux at center: 3,30 lx

*Lux distribution on a surface when lamp is mounted at 10 meters from the surface.*

**Potência**


**Vttagem: 12,0 V**

**Corrente: 0,400 A**

**Frequência: 0 Hz**

**FP: 0,99**

**THD**



**THD corrente: n/a**

**THD tensão: n/a**