

P50 SLED9017 BRANCA FITA 15WM 2400K 95 - 1m



Luminária linear pendente com iluminação difusa.
Corpo em alumínio extrudado com acabamento na cor branca. Difusor em acrílico extrudado leitoso. Indicado para residência, recepção, escritório etc.

Fluxo luminoso – 576 lm/m

Potência – 15,6 W/m

Intensidade pico – 240cd

CCT – 2442K



IRC – 96,1

Coordenada CIE 1931 – x- 0,488 y- 0,423

A x L - 50x50

Peso - 1,1kg/m


IP - 20 - Uso Interno

IK - 00 – Não aplicável

Alimentação - 12vdc

Data do ensaio

27/02/2023 14:27:18



Facho de abertura

98,1°


Rf 94,1



Fidelity index Rf

Rg 96,9


Gamut index Rg

		Shifts (%)	
Hue Bin	R _f	Chroma	Hue
1	94	-3%	0%
2	95	-3%	0%
3	95	-2%	0%
4	93	-5%	-2%
5	95	-4%	2%
6	94	-2%	4%
7	94	-3%	2%
8	95	0%	3%
9	95	-1%	3%
10	95	0%	3%
11	95	2%	3%
12	94	2%	-1%
13	92	1%	-8%
14	91	0%	-6%
15	94	-2%	-1%
16	91	-3%	-5%






TM-30: 94,1



CRI: 96,1 (R1-R8)



CRIRA R1-R8 / CRIR R1-R15

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
96,8	97,7	96,6	98,0	96,5	99,0	95,6	88,8	74,0	93,2	99,0	90,5	97,1	96,9	92,4

TM30 valores C. 16 valores extraídos dos 99.

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
94,0	95,4	94,9	93,3	94,9	93,9	94,2	95,0	95,3	94,8	95,2	94,2	91,7	90,9	94,4	91,3

Parametros de cor

Temperatura de cor	Índice de reprodução de cor	Reprodução de cor vermelho R9	Color fidelity	Color gamut	Color quality scale	Coordenada de cor cie 1931	Coordenada de cor cie 1931	Coordenada de cor	Coordenada de cor	Color deviation from black body
CCT	IRC	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2442 K	96,1	74,0	94,1	96,9	88,7	0,488	0,423	0,275	0,358	0,0028







Rf 94,1

Fidelity index Rf

Rg 96,9

Gamut index Rg

Hue Bin	R _i	Shifts (%)	
		Chroma	Hue
1	94	-3%	0%
2	95	-3%	0%
3	95	-2%	0%
4	93	-5%	-2%
5	95	-4%	2%
6	94	-2%	4%
7	94	-3%	2%
8	95	0%	3%
9	95	-1%	3%
10	95	0%	3%
11	95	2%	3%
12	94	2%	-1%
13	92	1%	-8%
14	91	0%	-6%
15	94	-2%	-1%
16	91	-3%	-5%



Avaliação todas as amostras de cores

Glare Evaluation According to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	18,1	19,2	18,4	19,6	19,8	16,7	17,8	17,0	18,2	18,4
	3H	19,4	20,6	19,9	20,9	21,1	17,4	18,6	17,8	18,9	19,1
	4H	20,0	21,1	20,4	21,4	21,7	17,6	18,7	18,0	19,0	19,3
	6H	20,4	21,3	20,7	21,6	22,0	17,7	18,7	18,0	19,0	19,4
	8H	20,4	21,4	20,8	21,7	22,1	17,7	18,6	18,0	19,0	19,4
	12H	20,5	21,4	20,9	21,7	22,2	17,7	18,6	18,0	18,9	19,4
4H	2H	18,4	19,5	18,9	19,8	20,1	17,3	18,4	17,7	18,7	19,0
	3H	20,0	20,9	20,4	21,3	21,8	18,3	19,2	18,6	19,5	20,0
	4H	20,6	21,4	21,0	21,8	22,4	18,4	19,3	18,9	19,7	20,2
	6H	21,0	21,8	21,5	22,2	22,6	18,5	19,3	19,0	19,7	20,1
	8H	21,1	21,8	21,6	22,2	22,6	18,5	19,2	19,0	19,6	20,0
	12H	21,2	21,8	21,7	22,2	22,7	18,5	19,1	19,0	19,5	20,0
8H	4H	20,6	21,3	21,1	21,7	22,1	18,6	19,3	19,1	19,7	20,1
	6H	21,1	21,7	21,6	22,1	22,7	18,7	19,3	19,3	19,8	20,3
	8H	21,3	21,8	21,8	22,3	23,0	18,8	19,3	19,4	19,8	20,5
	12H	21,4	21,8	22,0	22,3	22,9	18,8	19,2	19,4	19,8	20,4
12H	4H	20,6	21,2	21,1	21,6	22,1	18,6	19,2	19,1	19,6	20,1
	6H	21,1	21,6	21,7	22,1	22,8	18,8	19,2	19,3	19,8	20,5
	8H	21,3	21,7	21,9	22,2	22,8	18,8	19,2	19,4	19,8	20,4
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,1 / -0,1					0,2 / -0,3				
S = 1.5H		0,2 / -0,3					0,5 / -0,8				
S = 2.0H		0,7 / -0,9					1,0 / -1,6				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 576 lm total luminous flux											


Coeficiente de utilização

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	109	105	101	98	107	103	99	96	98	95	93	94	92	90	90	88	87	85
2	100	93	86	81	98	91	85	80	87	82	78	83	79	76	80	77	74	72
3	92	82	74	68	89	80	73	68	77	71	66	74	69	65	72	67	64	61
4	84	73	65	59	82	72	64	58	69	62	57	67	61	56	64	59	55	53
5	78	66	57	51	76	65	57	51	62	55	50	60	54	49	58	53	49	46
6	72	59	51	45	70	58	50	44	56	49	44	55	48	43	53	47	43	41
7	67	54	46	40	65	53	45	40	52	44	39	50	44	39	49	43	38	36
8	63	49	41	36	61	49	41	35	47	40	35	46	40	35	45	39	35	33
9	58	46	38	32	57	45	37	32	44	37	32	42	36	32	41	36	31	30
10	55	42	34	29	54	42	34	29	40	34	29	39	33	29	38	33	29	27

Quantidade de luminárias

Luminaire budgetary diagram





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
240lx	60lx	27lx	15lx	10lx	7lx	5lx	4lx	3lx	2lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx
22,3fcd	5,6fcd	2,5fcd	1,4fcd	0,9fcd	0,6fcd	0,5fcd	0,3fcd	0,3fcd	0,2fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
240	239	235	228	218	207	194	179	164	147	129	112	93	74	55	37	21	7	1	1
100%	100%	98%	95%	91%	86%	81%	75%	68%	61%	54%	47%	39%	31%	23%	15%	9%	3%	1%	1%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
240	238	233	225	214	199	182	163	143	124	104	84	64	46	28	15	7	3	1	2
100%	99%	97%	94%	89%	83%	76%	68%	60%	52%	43%	35%	27%	19%	12%	6%	3%	1%	1%	1%

Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
240	239	235	228	218	207	194	179	164	147	129	112	93	74	55	37	21	7	1	1
100%	100%	98%	95%	91%	86%	81%	75%	68%	61%	54%	47%	39%	31%	23%	15%	9%	3%	1%	1%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
240	238	233	225	214	199	182	163	143	124	104	84	64	46	28	15	7	3	1	2
100%	99%	97%	94%	89%	83%	76%	68%	60%	52%	43%	35%	27%	19%	12%	6%	3%	1%	1%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
98,1°	149,1°	165,2°	83,0%	59,2%

iso-candela diagram




10%	24 cd
20%	48 cd
30%	72 cd
40%	96 cd
50%	120 cd
60%	144 cd
70%	168 cd
80%	192 cd
90%	216 cd

Conditions:

Number of c-planes: 16

Candela at center: 240 cd

iso-lux diagram



3%	72,0m lx
5%	0,120 lx
10%	0,240 lx
30%	0,720 lx
50%	1,20 lx

Conditions:

Number of c-planes: 16

Lux at center: 2,40 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.

Potência

Vttagem: 12,0 V

Corrente: 1,30 A

Frequência: 0 Hz

FP: 1,0

THD



THD corrente: n/a

THD tensão: n/a