

P50 SLED9017 BRANCA FITA 15WM 2700K 95 - 1m



Luminária linear pendente com iluminação difusa.
Corpo em alumínio extrudado com acabamento na cor branca. Difusor em acrílico extrudado leitoso. Indicado para residência, recepção, escritório etc.

Fluxo luminoso – 584 lm/m

Potência – 15,0 W/m

Intensidade pico – 234cd

CCT – 2727K



IRC – 96,4

Coordenada CIE 1931 – x- 0,461 y- 0,416

A x L - 50x50

Peso - 1,1kg/m


IP - 20 - Uso Interno

IK - 00 – Não aplicável

Alimentação - 12vdc

Data do ensaio

16/03/2023 09:11:15



Facho de abertura

100,2°


Rf 94,9



Fidelity index Rf

Rg 99,1


Gamut index Rg

		Shifts (%)	
Hue Bin	R _f	Chroma	Hue
1	95	-3%	0%
2	97	-2%	0%
3	96	-1%	1%
4	96	-2%	0%
5	96	-2%	2%
6	97	0%	2%
7	97	-1%	0%
8	98	0%	1%
9	97	-1%	2%
10	94	0%	4%
11	93	1%	5%
12	93	3%	-1%
13	94	1%	-4%
14	92	2%	-6%
15	95	-1%	-2%
16	91	-1%	-7%






TM-30: 94,9



CRI: 96,4 (R1-R8)



CRiRa R1-R8 / CRiRe R1-R15

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
97,3	97,7	96,1	98,3	96,7	97,8	96,6	91,0	78,0	93,0	99,2	86,7	97,5	96,7	94,1

TM30 valores C. 16 valores extraídos dos 99.

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
94,8	96,5	95,9	95,8	96,1	97,2	97,1	98,4	96,5	93,9	93,2	92,7	93,9	92,3	94,7	90,6

Parametros de cor

Temperatura de cor	Índice de reprodução de cor	Reprodução de cor vermelho R9	Color fidelity	Color gamut	Color quality scale	Coordenada de cor cie 1931	Coordenada de cor cie 1931	Coordenada de cor	Coordenada de cor	Color deviation from black body
CCT	IRC	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2727 K	96,4	78,0	94,9	99,1	93,9	0,461	0,416	0,261	0,353	0,0017







Rf 94,9

Fidelity index Rf

Rg 99,1

Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	95	-3%	0%
2	97	-2%	0%
3	96	-1%	1%
4	96	-2%	0%
5	96	-2%	2%
6	97	0%	2%
7	97	-1%	0%
8	98	0%	1%
9	97	-1%	2%
10	94	0%	4%
11	93	1%	5%
12	93	3%	-1%
13	94	1%	-4%
14	92	2%	-6%
15	95	-1%	-2%
16	91	-1%	-7%



Avaliação todas as amostras de cores

Glare Evaluation According to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	18,0	19,2	18,3	19,5	19,8	16,9	18,0	17,1	18,4	18,6
	3H	19,4	20,6	19,8	20,9	21,1	17,9	19,1	18,3	19,4	19,6
	4H	20,0	21,1	20,4	21,4	21,7	18,4	19,5	18,8	19,8	20,1
	6H	20,4	21,4	20,8	21,7	22,1	18,8	19,8	19,2	20,1	20,5
	8H	20,5	21,5	20,9	21,8	22,3	19,0	19,9	19,3	20,3	20,7
	12H	20,6	21,5	21,0	21,9	22,4	19,1	20,0	19,5	20,4	20,9
4H	2H	18,4	19,5	18,8	19,8	20,1	17,5	18,6	17,9	18,9	19,2
	3H	20,1	21,0	20,4	21,4	21,8	18,7	19,7	19,1	20,0	20,5
	4H	20,7	21,5	21,1	22,0	22,5	19,2	20,1	19,7	20,5	21,1
	6H	21,2	22,0	21,7	22,4	22,8	19,6	20,5	20,2	20,9	21,2
	8H	21,3	22,1	21,9	22,5	22,9	19,8	20,6	20,4	21,0	21,4
	12H	21,4	22,1	22,0	22,5	23,0	20,0	20,7	20,6	21,1	21,6
8H	4H	20,8	21,5	21,3	21,9	22,3	19,4	20,2	20,0	20,6	21,0
	6H	21,4	22,0	21,9	22,5	23,0	20,0	20,6	20,5	21,0	21,6
	8H	21,7	22,1	22,2	22,7	23,4	20,3	20,8	20,8	21,3	22,0
	12H	21,9	22,3	22,5	22,8	23,4	20,6	21,0	21,2	21,5	22,1
12H	4H	20,7	21,4	21,3	21,8	22,3	19,4	20,1	20,0	20,5	21,0
	6H	21,4	21,9	22,0	22,5	23,1	20,1	20,6	20,6	21,1	21,8
	8H	21,7	22,1	22,3	22,6	23,3	20,4	20,8	21,0	21,3	21,9
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,1 / -0,1					0,1 / -0,1				
S = 1.5H		0,2 / -0,2					0,2 / -0,4				
S = 2.0H		0,5 / -0,7					0,6 / -0,9				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 584 lm total luminous flux											


Coeficiente de utilização

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	109	104	100	96	106	102	98	95	97	94	91	93	91	88	89	87	85	83
2	99	91	85	79	97	89	83	78	86	81	76	82	78	74	79	75	72	70
3	91	81	73	66	88	79	72	66	76	70	64	73	68	63	70	66	62	60
4	83	72	63	57	81	70	62	56	68	61	55	65	59	54	63	58	53	51
5	77	64	56	49	75	63	55	49	61	54	48	59	52	47	57	51	47	45
6	71	58	49	43	69	57	49	43	55	48	42	53	47	42	52	46	41	39
7	66	53	44	38	64	52	44	38	50	43	38	49	42	37	47	41	37	35
8	61	48	40	34	60	47	40	34	46	39	34	45	38	33	43	37	33	31
9	57	44	36	31	56	44	36	31	42	35	30	41	35	30	40	34	30	28
10	54	41	33	28	53	40	33	28	39	32	28	38	32	27	37	31	27	26

Quantidade de luminárias

Luminaire budgetary diagram





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
233lx	58lx	26lx	15lx	9lx	6lx	5lx	4lx	3lx	2lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx
21,7fcd	5,4fcd	2,4fcd	1,4fcd	0,9fcd	0,6fcd	0,4fcd	0,3fcd	0,3fcd	0,2fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
233	231	227	221	212	201	189	175	160	144	128	110	92	74	56	38	22	10	3	1
100%	99%	97%	95%	91%	86%	81%	75%	69%	62%	55%	47%	40%	32%	24%	16%	9%	4%	1%	1%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
233	232	227	219	208	195	180	164	146	127	108	89	70	53	40	29	19	11	5	3
100%	99%	97%	94%	89%	84%	77%	70%	63%	54%	46%	38%	30%	23%	17%	12%	8%	5%	2%	1%

Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
233	231	227	221	212	201	189	175	160	144	128	110	92	74	56	38	22	10	3	1
100%	99%	97%	95%	91%	86%	81%	75%	69%	62%	55%	47%	40%	32%	24%	16%	9%	4%	1%	1%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
233	232	227	219	208	195	180	164	146	127	108	89	70	53	40	29	19	11	5	3
100%	99%	97%	94%	89%	84%	77%	70%	63%	54%	46%	38%	30%	23%	17%	12%	8%	5%	2%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
100,2°	154,4°	174,9°	80,4%	56,6%

iso-candela diagram




10%	23 cd
20%	47 cd
30%	70 cd
40%	93 cd
50%	117 cd
60%	140 cd
70%	163 cd
80%	187 cd
90%	210 cd

Conditions:

Number of c-planes: 16

Candela at center: 233 cd

iso-lux diagram



3%	70,0m lx
5%	0,117 lx
10%	0,233 lx
30%	0,700 lx
50%	1,17 lx

Conditions:

Number of c-planes: 16

Lux at center: 2,33 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.

Potência

Vttagem: 12,0 V

Corrente: 1,25 A

Frequência: 0 Hz

FP: 0,99

THD



THD corrente: n/a

THD tensão: n/a