

## 9005 SLED9005 BRANCA FITA 7,2WM 3000K 80 - 1m



Luminária linear de sobrepor em forro de gesso ou Dry-wall com iluminação difusa. Corpo em alumínio extrudado com acabamento na cor branca. Difusor em acrílico extrudado leitoso. Indicado para residência, recepção, escritório etc.

Fluxo luminoso – 604 lm/m

Potência – 8,2 W/m

Intensidade pico – 192cd

CCT – 2881K



IRC – 82,5

Coordenada CIE 1931 – x- 0,443 y- 0,400

A x L - 8x17

Peso - 0,12kg/m


IP - 20 - Uso Interno

IK - 00 – Não aplicável

Alimentação - 12vdc

Data do ensaio

25/08/2022 15:27:48



Facho de abertura

**116,8°**


**Rf 84,4**



Fidelity index Rf

**Rg 94,2**


Gamut index Rg

Hue Bin	R <sub>f</sub>	Shifts (%)	
		Chroma	Hue
1	78	-12%	2%
2	81	-8%	7%
3	80	-3%	10%
4	91	-2%	4%
5	93	0%	2%
6	93	0%	-3%
7	87	-7%	-4%
8	92	-5%	1%
9	86	-5%	7%
10	81	-2%	12%
11	83	2%	13%
12	86	7%	0%
13	86	4%	-10%
14	79	3%	-17%
15	84	-5%	-9%
16	74	-11%	-16%






TM-30: 84,4



CRI: 82,5 (R1-R8)



CRIRA R1-R8 / CRIR R1-R15

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
82,1	93,9	92,4	79,4	82,6	93,1	79,6	56,4	6,3	86,4	79,3	75,6	85,4	96,6	73,7

TM30 valores C. 16 valores extraídos dos 99.

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
78,4	80,8	79,8	90,7	93,5	93,2	86,6	91,5	86,1	81,0	82,9	85,8	85,7	78,6	83,5	74,5

## Parametros de cor

Temperatura de cor	Índice de reprodução de cor	Reprodução de cor vermelho R9	Color fidelity	Color gamut	Color quality scale	Coordenada de cor cie 1931	Coordenada de cor cie 1931	Coordenada de cor	Coordenada de cor	Color deviation from black body
CCT	IRC	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	$\Delta uv$
2881 K	82,5	6,3	84,4	94,2	81,7	0,443	0,400	0,256	0,347	-0,0022







**Rf 84,4**

Fidelity index Rf

**Rg 94,2**

Gamut index Rg

Hue Bin	R <sub>i</sub>	Shifts (%)	
		Chroma	Hue
1	78	-12%	2%
2	81	-8%	7%
3	80	-3%	10%
4	91	-2%	4%
5	93	0%	2%
6	93	0%	-3%
7	87	-7%	-4%
8	92	-5%	1%
9	86	-5%	7%
10	81	-2%	12%
11	83	2%	13%
12	86	7%	0%
13	86	4%	-10%
14	79	3%	-17%
15	84	-5%	-9%
16	74	-11%	-16%



Avaliação todas as amostras de cores

Glare Evaluation According to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X    Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	20,6	21,8	20,9	22,2	22,5	20,9	22,1	21,2	22,5	22,8
	3H	22,1	23,4	22,6	23,7	24,0	22,7	23,9	23,1	24,3	24,5
	4H	22,8	24,0	23,2	24,3	24,7	23,5	24,7	24,0	25,1	25,4
	6H	23,4	24,4	23,7	24,8	25,2	24,4	25,5	24,7	25,8	26,2
	8H	23,5	24,6	23,9	24,9	25,4	24,7	25,8	25,1	26,1	26,6
	12H	23,6	24,7	24,0	25,0	25,5	25,1	26,1	25,5	26,5	27,0
4H	2H	21,3	22,5	21,7	22,8	23,1	21,5	22,7	22,0	23,1	23,4
	3H	23,1	24,2	23,5	24,5	25,0	23,6	24,6	24,0	25,0	25,5
	4H	23,8	24,8	24,3	25,3	25,8	24,5	25,5	25,0	25,9	26,5
	6H	24,5	25,4	25,0	25,8	26,2	25,5	26,4	26,0	26,8	27,2
	8H	24,7	25,5	25,2	25,9	26,4	25,9	26,7	26,4	27,1	27,6
	12H	24,9	25,6	25,4	26,0	26,5	26,4	27,1	26,9	27,5	28,0
8H	4H	24,2	25,1	24,8	25,5	25,9	24,8	25,6	25,4	26,1	26,5
	6H	25,1	25,7	25,6	26,2	26,8	26,0	26,6	26,5	27,1	27,7
	8H	25,4	26,0	26,0	26,5	27,2	26,6	27,1	27,1	27,7	28,4
	12H	25,7	26,1	26,3	26,7	27,3	27,2	27,6	27,8	28,2	28,8
12H	4H	24,3	25,0	24,8	25,5	26,0	24,8	25,5	25,4	26,0	26,5
	6H	25,2	25,8	25,8	26,3	27,0	26,1	26,6	26,6	27,2	27,9
	8H	25,6	26,1	26,2	26,6	27,3	26,7	27,2	27,3	27,7	28,4
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,1 / -0,1					0,1 / -0,1				
S = 1.5H		0,1 / -0,2					0,1 / -0,1				
S = 2.0H		0,3 / -0,4					0,2 / -0,3				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 604 lm total luminous flux											


**Coeficiente de utilização**

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	118	118	118	118	115	115	115	115	110	110	110	104	104	104	100	100	100	97
1	107	102	97	93	104	99	95	91	95	91	88	90	87	85	86	84	82	79
2	97	88	81	75	94	86	79	74	82	76	72	78	74	70	75	71	68	65
3	88	77	68	62	85	75	67	61	72	65	60	69	63	58	66	61	57	54
4	80	68	59	52	78	66	58	51	64	56	50	61	55	49	58	53	48	46
5	74	61	51	45	72	59	51	44	57	49	43	55	48	43	52	47	42	40
6	68	54	45	39	66	53	45	38	51	44	38	49	42	37	47	41	37	35
7	63	49	40	34	61	48	40	34	47	39	33	45	38	33	43	37	33	30
8	59	45	36	30	57	44	36	30	43	35	30	41	34	29	40	34	29	27
9	55	41	33	27	53	40	33	27	39	32	27	38	31	26	37	31	26	24
10	51	38	30	25	50	37	30	24	36	29	24	35	29	24	34	28	24	22

**Quantidade de luminárias**

**Luminaire budgetary diagram**





### Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
191lx	48lx	21lx	12lx	8lx	5lx	4lx	3lx	2lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	0lx
17,8fcd	4,4fcd	2fcd	1,1fcd	0,7fcd	0,5fcd	0,4fcd	0,3fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0fcd	0fcd

### Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
191	190	187	184	178	171	163	153	142	131	117	104	89	74	58	43	27	14	6	1
100%	99%	98%	96%	93%	89%	85%	80%	74%	68%	61%	54%	47%	39%	31%	22%	14%	7%	3%	1%

### Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
191	191	189	185	180	173	164	155	144	132	120	106	93	79	64	50	36	25	16	10
100%	100%	99%	97%	94%	90%	86%	81%	75%	69%	62%	56%	48%	41%	33%	26%	19%	13%	8%	5%

### Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
191	190	187	184	178	171	163	153	142	131	117	104	89	74	58	43	27	14	6	1
100%	99%	98%	96%	93%	89%	85%	80%	74%	68%	61%	54%	47%	39%	31%	22%	14%	7%	3%	1%

### Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
191	191	189	185	180	173	164	155	144	132	120	106	93	79	64	50	36	25	16	10
100%	100%	99%	97%	94%	90%	86%	81%	75%	69%	62%	56%	48%	41%	33%	26%	19%	13%	8%	5%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
116,8°	170,8°	191,3°	73,0%	49,0%

iso-candela diagram




10%	19 cd
20%	38 cd
30%	57 cd
40%	77 cd
50%	96 cd
60%	115 cd
70%	134 cd
80%	153 cd
90%	172 cd

Conditions:

Number of c-planes: 16

Candela at center: 191 cd

iso-lux diagram



3%	57,4m lx
5%	95,7m lx
10%	0,191 lx
30%	0,574 lx
50%	0,957 lx

Conditions:

Number of c-planes: 16

Lux at center: 1,91 lx

*Lux distribution on a surface when lamp is mounted at 10 meters from the surface.*

**Potência**


**Vttagem: 12,0 V**

**Corrente: 0,680 A**

**Frequência: 0 Hz**

**FP: 0,99**

**THD**



**THD corrente: n/a**

**THD tensão: n/a**