

9005 SLED9005U BRANCA FITA 9,6WM 4000K 80-1m



Luminária linear de sobrepor em forro de gesso ou Dry-wall com iluminação difusa. Corpo em alumínio extrudado com acabamento na cor branca. Difusor em acrílico extrudado leitoso. Indicado para residência, recepção, escritório etc.

Fluxo luminoso – 824 lm/m

Potência – 9,6 W/m

Intensidade pico – 189cd

CCT – 3921K



IRC – 82,6

Coordenada CIE 1931 – x- 0,385 y- 0,382

A x L - 8x17

Peso - 0,12kg/m


IP - 20 - Uso Interno

IK - 00 – Não aplicável

Alimentação - 12vdc

Data do ensaio

09/09/2022 11:28:42



Facho de abertura

129,5°


Rf 84,2



Fidelity index Rf

Rg 96,4


Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	80	-12%	-1%
2	83	-8%	6%
3	77	-4%	12%
4	87	1%	8%
5	90	3%	5%
6	93	4%	-2%
7	92	-2%	-4%
8	90	-5%	-2%
9	88	-7%	4%
10	79	-8%	10%
11	78	1%	14%
12	82	5%	8%
13	86	8%	-5%
14	87	9%	-7%
15	80	0%	-14%
16	78	-5%	-13%






TM-30: 84,2



CRI: 82,6 (R1-R8)



CRIRA R1-R8 / CRIR R1-R15

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
80,8	88,0	93,9	82,6	80,8	83,8	86,3	64,6	7,4	71,7	81,8	61,8	82,4	96,6	73,7

TM30 valores C. 16 valores extraídos dos 99.

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
80,5	83,3	76,9	86,7	89,5	93,3	92,1	90,0	88,3	78,7	78,2	81,9	85,9	87,5	80,3	78,3

Parametros de cor

Temperatura de cor	Índice de reprodução de cor	Reprodução de cor vermelho R9	Color fidelity	Color gamut	Color quality scale	Coordenada de cor cie 1931	Coordenada de cor cie 1931	Coordenada de cor	Coordenada de cor	Color deviation from black body
CCT	IRC	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3921 K	82,6	7,4	84,2	96,4	82,3	0,385	0,382	0,226	0,337	0,0013







Rf 84,2

Fidelity index Rf

Rg 96,4

Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	80	-12%	-1%
2	83	-8%	6%
3	77	-4%	12%
4	87	1%	8%
5	90	3%	5%
6	93	4%	-2%
7	92	-2%	-4%
8	90	-5%	-2%
9	88	-7%	4%
10	79	-8%	10%
11	78	1%	14%
12	82	5%	8%
13	86	8%	-5%
14	87	9%	-7%
15	80	0%	-14%
16	78	-5%	-13%



Avaliação todas as amostras de cores

Glare Evaluation According to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	19,2	20,3	19,7	20,9	21,5	21,1	22,2	21,6	22,8	23,4
	3H	20,6	21,7	21,2	22,3	22,8	23,4	24,5	24,0	25,1	25,6
	4H	21,1	22,2	21,7	22,7	23,4	24,6	25,6	25,2	26,2	26,8
	6H	21,5	22,4	22,1	23,0	23,7	25,9	26,8	26,5	27,4	28,1
	8H	21,6	22,5	22,1	23,1	23,8	26,6	27,5	27,2	28,1	28,8
	12H	21,6	22,5	22,2	23,1	23,8	27,4	28,4	28,0	28,9	29,6
4H	2H	20,2	21,3	20,9	21,9	22,5	21,6	22,7	22,3	23,3	23,9
	3H	21,9	22,9	22,6	23,5	24,2	24,2	25,2	24,8	25,8	26,5
	4H	22,6	23,6	23,2	24,1	24,9	25,5	26,6	26,2	27,1	27,9
	6H	23,0	23,9	23,8	24,5	25,2	27,0	27,8	27,7	28,4	29,1
	8H	23,2	23,9	23,9	24,5	25,2	27,8	28,5	28,5	29,2	29,9
	12H	23,3	23,8	24,0	24,5	25,3	28,7	29,3	29,5	30,0	30,8
8H	4H	23,4	24,1	24,1	24,7	25,4	25,8	26,5	26,5	27,2	27,9
	6H	24,1	24,7	24,9	25,4	26,2	27,6	28,1	28,3	28,8	29,7
	8H	24,4	24,9	25,2	25,7	26,6	28,6	29,0	29,3	29,8	30,7
	12H	24,6	25,0	25,4	25,8	26,6	29,7	30,1	30,5	30,9	31,7
12H	4H	23,6	24,2	24,3	24,9	25,6	25,8	26,4	26,5	27,1	27,9
	6H	24,5	25,0	25,3	25,8	26,7	27,6	28,1	28,4	28,9	29,8
	8H	24,9	25,3	25,7	26,1	27,0	28,7	29,1	29,5	29,9	30,7
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,1 / -0,1					0,1 / -0,1				
S = 1.5H		0,2 / -0,2					0,1 / -0,1				
S = 2.0H		0,3 / -0,5					0,2 / -0,2				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 824 lm total luminous flux											


Coeficiente de utilização

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	115	115	115	115	110	110	110	110	101	101	101	93	93	93	85	85	85	82
1	103	97	92	88	98	93	88	84	85	82	78	78	75	73	72	69	67	64
2	92	83	76	70	88	80	73	67	73	68	63	67	63	59	62	58	55	52
3	84	73	64	57	80	70	62	55	64	57	52	59	53	49	54	49	46	43
4	76	64	55	48	73	61	53	46	56	49	44	52	46	41	48	43	39	36
5	70	57	47	40	66	54	46	39	50	43	37	46	40	35	43	37	33	31
6	64	51	42	35	61	49	40	34	45	38	32	42	35	31	38	33	29	26
7	60	46	37	31	57	44	36	30	41	34	28	38	32	27	35	30	26	23
8	55	42	33	27	53	40	32	26	37	30	25	35	28	24	32	27	23	21
9	52	38	30	24	49	37	29	24	34	27	23	32	26	21	30	24	20	18
10	48	35	27	22	46	34	26	21	32	25	20	29	24	19	27	22	18	17

Quantidade de luminárias

Luminaire budgetary diagram





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
187lx	47lx	21lx	12lx	7lx	5lx	4lx	3lx	2lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	1lx	0lx
17,4fcd	4,3fcd	1,9fcd	1,1fcd	0,7fcd	0,5fcd	0,4fcd	0,3fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
187	184	176	162	143	122	97	70	43	15	3	3	2	3	2	2	2	2	2	2
100%	98%	94%	87%	76%	65%	52%	37%	23%	8%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%

Intensities in 90° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
187	189	188	182	171	156	138	117	93	70	57	53	49	44	39	33	26	19	11	3
100%	101%	100%	97%	91%	83%	74%	63%	50%	38%	30%	28%	26%	24%	21%	18%	14%	10%	6%	1%

Intensities in 180° c-plane


0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
187	184	176	162	143	122	97	70	43	15	3	3	2	3	2	2	2	2	2	2
100%	98%	94%	87%	76%	65%	52%	37%	23%	8%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%

Intensities in 270° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
187	189	188	182	171	156	138	117	93	70	57	53	49	44	39	33	26	19	11	3
100%	101%	100%	97%	91%	83%	74%	63%	50%	38%	30%	28%	26%	24%	21%	18%	14%	10%	6%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
129,5°	254,1°	305,7°	56,8%	37,2%

iso-candela diagram



Horizontal angles


10%	19 cd
20%	37 cd
30%	56 cd
40%	75 cd
50%	94 cd
60%	112 cd
70%	131 cd
80%	150 cd
90%	169 cd

Conditions:

Number of c-planes: 16

Candela at center: 187 cd

iso-lux diagram



Mounting height: 10 meters

3%	56,2m lx
5%	93,6m lx
10%	0,187 lx
30%	0,562 lx
50%	0,936 lx

Conditions:

Number of c-planes: 16

Lux at center: 1,87 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.

Potência

Vttagem: 12,0 V

Corrente: 0,800 A

Frequência: 0 Hz

FP: 1,0

THD



THD corrente: n/a

THD tensão: n/a