


EX06 SLED9161 BRANCA FITA 9,6WM 5500K 80 - 1m



Luminária linear de sobrepor em mobiliário com iluminação difusa. Corpo em borracha com acabamento na cor branca. Difusor em borracha leitosa. Indicado para residência, mobiliário etc.

Fluxo luminoso – 280 lm/m

Potência – 9,6 W/m

Intensidade pico – 94,4cd

CCT – 4400K



IRC – 86,0

Coordenada CIE 1931 – x- 0,365 y- 0,366

A x L - 12x6

Peso - 0,26kg/m


IP - 20 - Uso Interno

IK - 00 – Não aplicável

Alimentação - 12vdc

Data do ensaio

18/11/2020 10:04:08



Facho de abertura

114,2°


Rf 83,6



Fidelity index Rf

Rg 93,1


Gamut index Rg

Hue Bin	R _f	Shifts (%)	
		Chroma	Hue
1	77	-12%	2%
2	86	-6%	6%
3	85	-4%	7%
4	88	-3%	2%
5	88	-5%	0%
6	93	-3%	-1%
7	87	-8%	1%
8	82	-8%	6%
9	81	-7%	16%
10	74	-2%	16%
11	78	5%	13%
12	92	5%	-1%
13	86	6%	-9%
14	84	0%	-10%
15	72	3%	-24%
16	86	-8%	-2%






TM-30: 83,6



CRI: 86,0 (R1-R8)



CRIRa R1-R8 / CRIRe R1-R15

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
86,0	94,5	95,0	82,5	84,8	88,6	86,1	70,2	21,4	84,8	82,5	59,9	89,5	98,2	81,0

TM30 valores C. 16 valores extraídos dos 99.

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
76,8	85,8	84,8	88,3	88,4	93,2	87,5	82,4	80,8	74,0	78,0	91,8	85,6	84,3	71,9	86,0

Parametros de cor

Temperatura de cor	Indice de reprodução de cor	Reprodução de cor vermelho R9	Color fidelity	Color gamut	Color quality scale	Coordenada de cor cie 1931	Coordenada de cor cie 1931	Coordenada de cor	Coordenada de cor	Color deviation from black body
CCT	IRC	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
4400 K	86,0	21,4	83,6	93,1	82,2	0,365	0,366	0,206	0,319	0,0023







Rf 83,6

Fidelity index Rf

Rg 93,1

Gamut index Rg

Hue Bin	R _i	Shifts (%)	
		Chroma	Hue
1	77	-12%	2%
2	86	-6%	6%
3	85	-4%	7%
4	88	-3%	2%
5	88	-5%	0%
6	93	-3%	-1%
7	87	-8%	1%
8	82	-8%	6%
9	81	-7%	16%
10	74	-2%	16%
11	78	5%	13%
12	92	5%	-1%
13	86	6%	-9%
14	84	0%	-10%
15	72	3%	-24%
16	86	-8%	-2%



Avaliação todas as amostras de cores

Glare Evaluation According to UGR


p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	18,4	19,7	18,7	20,0	20,3	18,5	19,7	18,7	20,0	20,3
	3H	19,9	21,2	20,4	21,5	21,7	20,1	21,3	20,5	21,6	21,9
	4H	20,6	21,8	21,0	22,1	22,4	20,8	22,0	21,2	22,3	22,6
	6H	21,1	22,1	21,4	22,4	22,8	21,4	22,5	21,8	22,8	23,2
	8H	21,2	22,2	21,5	22,5	23,0	21,7	22,7	22,0	23,0	23,5
	12H	21,2	22,3	21,6	22,6	23,1	21,8	22,8	22,2	23,2	23,7
4H	2H	19,1	20,3	19,5	20,6	20,9	19,1	20,3	19,5	20,6	20,9
	3H	20,9	21,9	21,3	22,3	22,7	21,0	22,0	21,4	22,4	22,9
	4H	21,6	22,5	22,0	22,9	23,5	21,8	22,7	22,3	23,2	23,7
	6H	22,1	23,0	22,6	23,4	23,8	22,5	23,4	23,0	23,8	24,2
	8H	22,3	23,1	22,8	23,5	23,9	22,8	23,6	23,3	24,0	24,4
	12H	22,4	23,1	22,9	23,5	24,0	23,0	23,7	23,5	24,1	24,6
8H	4H	21,9	22,7	22,4	23,1	23,5	22,1	22,9	22,6	23,3	23,7
	6H	22,6	23,2	23,1	23,7	24,3	23,0	23,6	23,5	24,1	24,7
	8H	22,9	23,4	23,4	24,0	24,6	23,4	23,9	23,9	24,5	25,1
	12H	23,1	23,5	23,7	24,1	24,7	23,7	24,2	24,3	24,7	25,3
12H	4H	21,9	22,6	22,4	23,0	23,5	22,1	22,8	22,6	23,2	23,7
	6H	22,7	23,3	23,3	23,8	24,5	23,1	23,6	23,6	24,2	24,8
	8H	23,0	23,5	23,6	24,0	24,6	23,5	24,0	24,1	24,5	25,1
Variation of the observer position for the luminaire distance S											
S = 1.0H		0,1 / -0,1					0,1 / -0,1				
S = 1.5H		0,1 / -0,2					0,1 / -0,2				
S = 2.0H		0,4 / -0,5					0,3 / -0,4				
Standard table		n/a					n/a				
Correction summand		n/a					n/a				
Corrected glare indices referring to 280 lm total luminous flux											


Coeficiente de utilização

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	101	101	101	99
1	108	103	99	95	105	101	97	93	96	93	90	92	89	87	88	86	84	82
2	98	89	82	76	95	87	81	75	84	78	73	80	76	72	77	73	70	67
3	89	78	70	63	86	77	69	63	73	67	61	70	65	60	68	63	59	56
4	81	69	60	53	79	68	59	53	65	58	52	62	56	51	60	55	50	48
5	75	62	52	46	72	60	52	45	58	51	45	56	49	44	54	48	43	41
6	69	55	46	40	67	54	46	39	52	45	39	50	44	39	49	43	38	36
7	64	50	41	35	62	49	41	35	47	40	34	46	39	34	44	38	34	32
8	59	46	37	31	58	45	37	31	43	36	31	42	35	30	41	35	30	28
9	55	42	33	28	54	41	33	28	40	33	27	39	32	27	38	31	27	25
10	52	38	30	25	50	38	30	25	37	30	25	36	29	25	35	29	24	23

Quantidade de luminárias

Luminaire budgetary diagram





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3,3ft	6,6ft	9,8ft	13,1ft	16,4ft	19,7ft	23ft	26,2ft	29,5ft	32,8ft	36,1ft	39,4ft	42,7ft	45,9ft	49,2ft	52,5ft	55,8ft	59,1ft	62,3ft	65,6ft
94lx	24lx	10lx	6lx	4lx	3lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx
8,7fcd	2,2fcd	1fcd	0,5fcd	0,3fcd	0,2fcd	0,2fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0,1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
94,2	94,1	92,6	90,8	87,9	84,3	80,2	75,2	69,7	63,6	56,8	50,0	42,5	34,5	26,4	18,2	10,6	4,4	0,8	0,5
100%	100%	98%	96%	93%	90%	85%	80%	74%	68%	60%	53%	45%	37%	28%	19%	11%	5%	1%	1%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
94,2	93,9	92,7	90,6	87,9	84,3	80,1	75,3	69,7	63,7	57,3	50,2	43,0	35,7	28,0	20,6	13,4	6,8	2,3	1,2
100%	100%	98%	96%	93%	90%	85%	80%	74%	68%	61%	53%	46%	38%	30%	22%	14%	7%	2%	1%

Intensities in 180° c-plane


0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
94,2	94,1	92,6	90,8	87,9	84,3	80,2	75,2	69,7	63,6	56,8	50,0	42,5	34,5	26,4	18,2	10,6	4,4	0,8	0,5
100%	100%	98%	96%	93%	90%	85%	80%	74%	68%	60%	53%	45%	37%	28%	19%	11%	5%	1%	1%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
94,2	93,9	92,7	90,6	87,9	84,3	80,1	75,3	69,7	63,7	57,3	50,2	43,0	35,7	28,0	20,6	13,4	6,8	2,3	1,2
100%	100%	98%	96%	93%	90%	85%	80%	74%	68%	61%	53%	46%	38%	30%	22%	14%	7%	2%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
114,2°	164,6°	177,8°	76,3%	50,7%

iso-candela diagram




10%	9 cd
20%	19 cd
30%	28 cd
40%	38 cd
50%	47 cd
60%	56 cd
70%	66 cd
80%	75 cd
90%	85 cd

Conditions:

Number of c-planes: 16

Candela at center: 94 cd

iso-lux diagram



3%	28,2m lx
5%	47,1m lx
10%	94,2m lx
30%	0,282 lx
50%	0,471 lx

Conditions:

Number of c-planes: 16

Lux at center: 0,942 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.

Potência

Vttagem: 12,0 V

Corrente: 0,800 A

Frequência: 0 Hz

FP: 1,0

THD



THD corrente: n/a

THD tensão: n/a